


SOMETHING WRONG



The Chaplain—Remember, stone walls do not a prison make, nor iron bars a cage.

The Convict—Well, then, you've got me hypnotized!



Jimmie—Where shall we say we were when we get home?

Willie—If they ask us we must tell the truth, of course.

Jimmie—Sure, but let's tell the same truth.



You shouldn't cry over split milk.

My friend, that remark originated when milk wasn't ten cents a pint.



You've got no kick about my extravagance. You were crazy to marry me.

I realize that now.



Would you marry a girl for her money?

I don't know. I haven't seen anything I couldn't buy that as yet.




What party do you belong to, Mr. Jones?

Oh, I'm not married.



Allice—Why didn't Kitty sing for you last night?

George—I did; didn't you see she didn't sing.



Did you throw any old shoes at the bride and groom?

No. To do that I'd have been obliged to take them off my feet.

A Jazzy Warning.

There are those who refuse to accept the conventional, no matter how expressed. Take the "I" utter of the warning signals now common on the backs of motor cars. Usually they read: "I am ready for the one word, "stop," but the other evening on Fifth and a standstill, the command, "Halt, Kid," flashed into view—Detroit News.

BUILDING CODE—ORDINANCE NO. 104 (Continued)

(a) Such room or booth shall be one of the following constructions: Brick, tile or concrete with walls, floor and ceilings not less than eight (8) inches thick. Thickness may be reduced to four (4) inches if reinforced concrete is used.

(b) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(c) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(d) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(e) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(f) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(g) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(h) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(i) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(j) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(k) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(l) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(m) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(n) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(o) The entrance door shall be constructed of either sheet iron or asbestos board not less than one-half (1/2) inch thick and shall be provided with automatic doors constructed of sheet metal or asbestos board.

(a) All plumbing and sewage work in the Village of Birmingham shall be under the control of the Village Commissioner, who shall appoint a properly qualified inspector of plumbing and house drainage.

(b) Such inspector shall hold office until the first day of April in the year following his appointment, and until his successor qualifies and enters upon the duties of the office.

(c) Such inspector shall be at all times under the direct control of the Village Commissioner, who shall have the power to suspend him from office, upon recommendation of the Manager, for incompetency or neglect of duty.

(d) The plumbing inspector shall make all inspections of plumbing installations, see that the proper returns are made by the plumber for each job, and keep an accurate record of same, and any other duties that may be required by his office.

(e) The plumbing inspector shall have the power to stop any plumbing work upon question arising under the provisions of this ordinance relating to plumbing inspection, except where otherwise provided and subjected to conditions contained in this ordinance.

(f) He shall have the power to stop work on any plumbing or sewage work which is being installed in violation of this ordinance and shall have authority to enter at any reasonable time, upon all public or private premises for the purpose of inspecting the same.

(g) He shall have the right, at any reasonable time, to enter any building for the purpose of inspecting the sanitary condition of same and should any defect be found in an unsanitary condition he shall have the power to order the owner, or occupant, thereof to remedy such unsanitary condition, in a reasonable length of time and in such a manner as shall comply with the conditions of this ordinance.

(h) All powers of the plumbing inspector, as defined in this section, are subject to the approval of the Village Manager, and no action shall be taken by the plumbing inspector until such approval has been secured.

ARTICLE II—Licenses.

Section 1.—APPLICATION FOR LICENSE.

(a) Any person, firm or corporation desiring to do business as a plumber in the Village of Birmingham, shall file in the office of the Village Clerk, a petition giving the name of the person, firm or corporation and their place of business, and asking to be licensed as a plumber.

(b) Such petition shall be accompanied by affidavits of members of the Village of Birmingham, vouching for the business capacity and reputation of the applicant, that he is a master of his trade and willing to be governed by all laws and regulations which are, or may be, adopted by the Commission of the said Village.

(c) An applicant for a license shall execute and deposit with his application a bond with two (2) or more resident sureties, to be approved by said commission, in the sum of five hundred (\$500.00) dollars, or such amount that the Commission may from time to time designate. Such bond may be issued by a surety company, instead of the resident surety, with the approval of the Commission.

(d) Such bond shall be conditioned that the applicant for license will indemnify and save harmless the Village of Birmingham from all accidents and damages, caused by any negligence in protecting his work, or by any unlawful, improper, inadequate or careless work done by him, and that he will properly and lawfully conduct his business in the streets, alleys and street or alley surfaces over any opening he may have made, made to, as good a state and condition as he found it previous to opening the same, and will maintain and repair the same in conformity with the requirements of the Commission for the period of six (6) months next thereafter, and that he will pay all fines imposed on him for violation of any of the rules and regulations prescribed in this Ordinance.

Section 2.—BOND.

(a) Upon receiving his license the applicant shall pay a fee of twenty-five (\$25.00) dollars and shall have recorded in the office of the Village Clerk his actual place of business for the purpose of original application, and he shall notify the Village Clerk of any change in either of these matters.

(b) No license shall be granted for more than one (1) year and all licenses will be granted to expire on the first Monday in June. Renewal of license for a period of five (5) years after date of original application may be made by the applicant in accordance with the original application and paying a renewal fee of one (\$100.00) dollar. At the expiration of each five (5) years period the license shall be renewed under the same terms and conditions as the original application, and the fee for such renewal shall be twenty-five (\$25.00) dollars, the same as for original license.

Section 3.—LICENSE FEE.

(a) Upon receiving his license the applicant shall pay a fee of twenty-five (\$25.00) dollars and shall have recorded in the office of the Village Clerk his actual place of business for the purpose of original application, and he shall notify the Village Clerk of any change in either of these matters.

(b) No license shall be granted for more than one (1) year and all licenses will be granted to expire on the first Monday in June. Renewal of license for a period of five (5) years after date of original application may be made by the applicant in accordance with the original application and paying a renewal fee of one (\$100.00) dollar. At the expiration of each five (5) years period the license shall be renewed under the same terms and conditions as the original application, and the fee for such renewal shall be twenty-five (\$25.00) dollars, the same as for original license.

Section 4.—LICENSING.

(a) Upon receiving his license the applicant shall pay a fee of twenty-five (\$25.00) dollars and shall have recorded in the office of the Village Clerk his actual place of business for the purpose of original application, and he shall notify the Village Clerk of any change in either of these matters.

(b) No license shall be granted for more than one (1) year and all licenses will be granted to expire on the first Monday in June. Renewal of license for a period of five (5) years after date of original application may be made by the applicant in accordance with the original application and paying a renewal fee of one (\$100.00) dollar. At the expiration of each five (5) years period the license shall be renewed under the same terms and conditions as the original application, and the fee for such renewal shall be twenty-five (\$25.00) dollars, the same as for original license.

Section 5.—LICENSING.

(a) Upon receiving his license the applicant shall pay a fee of twenty-five (\$25.00) dollars and shall have recorded in the office of the Village Clerk his actual place of business for the purpose of original application, and he shall notify the Village Clerk of any change in either of these matters.

(b) For such test the iron extension of the soil pipe outside the building shall be securely closed, together with all branches, inlets and other highest opening above the roof with wads of the pipes filled to the top of the pipe with a mixture of cement and sand. For this test regular test plugs may be used as a wooden or other make-shaft pipes will not be permitted, the work will be accepted.

(c) If, in consequence, or impracticability, to test the entire work at once, it is sectioned off for each extra inspection the plumber shall be charged a fee of \$10.00.

(d) If any part of the work is tested separately it must withstand a tested, or full-water pressure, and no test shall be made for including any joints or connections in at least one test.

ARTICLE VI—Definition of Terms.

Section 1.—HOUSE SEWER.

(a) The term "House Sewer" is applied to that part of the outer wall or sewer extending from a point two (2) feet outside of the outer wall to the building to its connection with a public sewer, private sewer, septic tank or cesspool.

Section 2.—HOUSE DRAIN.

(a) The term "House Drain" is applied to that part of the main horizontal drain and its branches inside the walls of the building and extending to and connecting with the house sewer.

Section 3.—SOIL PIPE.

(a) The term "Soil Pipe" is applied to any vertical line of pipe extending through the roof and receiving the discharge of one or more water closets, with or without fixtures.

Section 4.—WASTE PIPE.

(a) The term "Waste Pipe" is applied to any pipe extending through the roof and receiving the discharge from any fixture except water closets, and is not a soil pipe.

Section 5.—WATER PIPE.

(a) The term "Water Pipe" is applied to any special pipe provided to ventilate the system of piping and to prevent transpiration and back pressure.

ARTICLE VII—Rules and Regulations.

Section 1.—GENERAL.

(a) All plumbing and sewerage work in the Village of Birmingham shall be installed in accordance with the best modern practice and in accordance with the following regulations:

(b) All materials and workmanship shall be first class in all respects.

Section 2.—HOUSE SEWER.

(a) The house sewer shall be evenly laid with a uniform fall from the end of the house drain to the main sewer, and no line shall be laid with less than one (1) inch fall per foot.

(b) The entire sewer shall be laid in a straight line as possible, and shall have solid support for the hub end of the pipe. All changes in direction shall be made by the use of 90 degree elbows.

(c) All joints shall be made with fresh mastic or Portland cement mortar, not more than two (2) parts sand being used to one (1) part of cement. All joints shall be properly cleaned and then cemented on the outside by means of a scrub or scraper.

(d) The outside wall of the soil pipe shall be used nearest two (2) feet from the wall, and in no case shall the sewer pipe from one building cross under another or lateral sewer.

Section 3.—SPECIFICATIONS.

(a) All sewer pipe shall be vitrified earthenware, hard burned, eight (8) inches internal diameter. No sewer pipe shall be less than four (4) inches external diameter.

(b) The entire sewer shall be laid in a straight line as possible, and shall have solid support for the hub end of the pipe. All changes in direction shall be made by the use of 90 degree elbows.

(c) All joints shall be made with fresh mastic or Portland cement mortar, not more than two (2) parts sand being used to one (1) part of cement. All joints shall be properly cleaned and then cemented on the outside by means of a scrub or scraper.

(d) The outside wall of the soil pipe shall be used nearest two (2) feet from the wall, and in no case shall the sewer pipe from one building cross under another or lateral sewer.

Section 4.—SPECIFICATIONS.

(a) All sewer pipe shall be vitrified earthenware, hard burned, eight (8) inches internal diameter. No sewer pipe shall be less than four (4) inches external diameter.

(b) The entire sewer shall be laid in a straight line as possible, and shall have solid support for the hub end of the pipe. All changes in direction shall be made by the use of 90 degree elbows.

(c) All joints shall be made with fresh mastic or Portland cement mortar, not more than two (2) parts sand being used to one (1) part of cement. All joints shall be properly cleaned and then cemented on the outside by means of a scrub or scraper.

(d) The outside wall of the soil pipe shall be used nearest two (2) feet from the wall, and in no case shall the sewer pipe from one building cross under another or lateral sewer.

Section 5.—SPECIFICATIONS.

(a) All sewer pipe shall be vitrified earthenware, hard burned, eight (8) inches internal diameter. No sewer pipe shall be less than four (4) inches external diameter.

(b) The entire sewer shall be laid in a straight line as possible, and shall have solid support for the hub end of the pipe. All changes in direction shall be made by the use of 90 degree elbows.

(c) All joints shall be made with fresh mastic or Portland cement mortar, not more than two (2) parts sand being used to one (1) part of cement. All joints shall be properly cleaned and then cemented on the outside by means of a scrub or scraper.

(d) The outside wall of the soil pipe shall be used nearest two (2) feet from the wall, and in no case shall the sewer pipe from one building cross under another or lateral sewer.

(e) All sewer pipe shall be vitrified earthenware, hard burned, eight (8) inches internal diameter. No sewer pipe shall be less than four (4) inches external diameter.