BUILDING CODE—Ordinance No. 12

(Continued From Preceding Page)
ARTICLE X—STOVES AND RANGES
—COAL OR WOOD STOVES AND RANGES.
Kitchen ranges, or any description, of stove used for heatsees, shall not be placed nearer than twelve (12) inches to
or partition constructed of combustible materials unless
is protected as hereinafter specified.

materials shall be

(6)

subject to automatic ignition must be provided matic device, so designed that oil, upon being stion chamber, will immediately become ignited, off.

(b) No balcony shall project more than four (4) feet over any stidewalk nor shall be less than twelve (12) feet above the sidewalk leads to the sidewalk and the provided, that not to exceed four feet stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that not to exceed four feet stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that not to exceed four feet stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that not to exceed four feet stidewalk nor shall be less than twelve (12) feet over any stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that not to exceed four feet stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that not to exceed four feet stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that not to exceed four feet stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that not to exceed four feet stidewalk nor shall be less than twelve (12) feet above the sidewalk leads and the provided that the provide

of a minimo...
of size as given in the
no bullon...

Thickness of Material
14 gauge stories in any kind of bt
12 gauge statis not less than two (2
7 gauge
14 gauge
15-16 gauge
16-16 gauge
17 gauge
18-10 gauge
19-10 gauge
1

single residences, private garages, and for small outbuildings, if located nation as the state of the state o

tion.

Section 2.—BAY WINDOWS.

(a) Bay windows in Zone No. 1 may be constructed of wood two shall any carries in height and not extending above the 3rd floor.

(b) In no case will bay windows constructed of wood be allowed above the 2nd story.

porches, these porches

cornices projecting over any sidewalk shall section 1.—MAJOR ter edge or shall have the top surface sloping (a) The defin to prevent water from dripping to the side shall be as specified.

velve (12) inches. lusive of above projections

nd shall be easily opened from the inside at all times without the e of a kee;
settler 4. All building of Class 1 and 2 over two (2) stories in height to be only the control of the cont

ARTICLE XV—THEATERS

Section 1.—MAJOR THEATERS.

(a) The definition of, and requirements for, Major Theaters shall be as specified by the Building Code of the City of Detroit, Mich-

hall not be more than six (6) seats between any sext and aide not more than thirteen (13) seats between any sext and aide not expected the sext and All seats shall be securely fastened to the floor and there he more than six (6) seats between any seat and aisle nor

tool tess than six (6) feet x eight, of one of the following contibution of the following contibution of the following contibution of the following contibution of the following the fol

(f) All shelves, furniture and fixtures within the booth shall be constructed of non-combustible material.

(g) Each booth must have an opening in the top at least ten (10) nehes in diameter to provide for ventilation. Such opening shall have a pipe rading to a chinque, or to the outer air, or cometed to

Each machine must be securely fastened to the floor to pre-

manner to prevent its coming bit.

manner to prevent its coming bit.

manner to prevent its coming bit.

manner to manner to manner to the thing t

-PUBLIC GARAGES

ARTICLE XVI—PUBLIC GARAGES

The term "Fluible Garage" shall be construed to mean a
The term "rather Garage" shall be construed to mean a
like of motor cars designed for the use of inflammable liquids
or power.

Whete any portion, of a building is used for such purpose
ge shall be deemed to include all of the building not separated
2—CONSTRUCTION above fire walls. building, or

(b) Where any posterior to the garage shall be deemed to include all of the bundles from the garage proper by suitable fire walls.

Section 2.—COMSTRUCTION of cither types 1, 2, 3, or 6 construction (a) Public garages may be of cither types 1, 2, 3, or 6 construction (b) Public garages may be for the construction of the cons

(c) All rooms having an occupancy of more than seventy, and the provided that if such building is over one (1) story in height but as the control of the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height but as the provided that if such building is over one (1) story in height building in over one (1) story in height building is over one (1) story in height building in over one (1) story in height building