(Continued from Preceding Page)

to automatically maintain the solvent liquid level in the still at the proper height.

Fittings.—Pitings.—Piting and fittings shall be full-weight wrought from or the equivalent. Where unions are used they shall be full even to the approved hazardous liquid type. All plping shall be tested to a pressure of at least 50 pounds per squares inch and proved tight of \$60.33 Valrea—All valves handling solvent shall be of the type approved for hazardous liquids or of the type incorporating an unthreaded, shouldeed, beveld packing gland stuffing box.

600.34 Serabbing Tubs & Hrushing Tubes.—Articles, Character Serabbing Tubs & Hrushing Tubes.—Articles, exclusive the service of t

nd tanks, or to approve constants.

willable.

uring or Brushing Operations.—All scouring or brush

s shall be carried on in the dry cleaning room or in a

resistive compartment with wall openings to the out-

Scouring or Bunshing—Ventilation—The scouring or brushor scrubbing tub shall be so located as to ensure through
twe disposal of vapors through the ventilating system.

Scouring or Brushing Table—The scouring or brushing
or brushing Table—The scouring or brushing
the bunshing or brushing table to be so the bunshing or brushing to approved container or to a 1½ inch drain
n with liquid seal trap direct to underground tank. Metal
re used shall be liquid-tight and permanently and effectively
The table shall be sequred to the floor or wall so as not to nen high. The top of the table shall be so pitched as to orough draining to approved container or to a 1½ inch drain as the shall be set to underground tank. Metal which is the shall be setured to the floor or wall so as not to Spotting—Hammable Solvent.—Flammable solvents used in a with spotting operations shall be limited to 1 gallon and from approved safety gans. Storage shall be in approved metal to the shall be set to the shall be a spotting—Hammable solvents used in with spotting operations shall be limited to 1 gallon and from approved safety gans. Storage shall be in approved and the shall be shall be shall be shall be a spotting and the shall be shall be shall be shall be a spotting and the shall be sh

co as to anzarus involved in their departments and they perform.

—All clothes when received at the plant shall be d in the receiving room and all foreign materials, and metallic substances, removed:

Albahur Removal from Washer——It removing the batch of from a washer excess solvent shall be drained from the to provent spillage on the floor. Pleor Drains—No open floor drains are permitted direct a missis installed with an approved type intercepter.

Simoking—Smoking on the premises shall be strictly promoting—Smoking—Smoking on the premises shall be strictly promoting—Smoking—Smoking on the premises shall be strictly promoting—Smoking—Smoking—Smoking in the premises of the floor of NO SMOKING signs shall be posted. ermoved from all set the close of the day's work, deposited in approved waste moved from the premises, and safely disposed of. At all nest the trap covers shall be kept securely in place.

ing solvents classified as non-flammable, or as non-ridinary temperatures and only slightly flammable at ures, shall be designated as class III installations, and the following requirements: leaning Building.—Dry cleaning systems which utilize by within the scope of the above definition and

n. Fire Extinguishers.—In addition to the regular first aid ining equipment required to meet the general needs of the east of the season of the season of the season of the sea shall be provided for every room or area in which dry or spotting operations are carried on. These may be hand ners, and if necessary, wheeled extinguishers, depending upon blant in any-cases, at least 1 extinguisher shall be deep control of the season of the season of the season of the edge of the season of the season of the season of the season of the edge of the season of the season of the season of the season of the edge of the season of the season of the season of the season of the edge of the season of the season of the season of the season of the edge of the season of the season of the season of the season of the edge of the season of the season of the season of the season of the edge of the season of the

at each entrance of every room, area or possible to the dependent plant. Pire flazards.—All persons sengaged in dry cleaning shall multiple flazards.—All persons sengaged in dry condition, free from multation of drir, waste garden and sanitary conditions, and in multation of drir, waste garden person of the property of the property

CHAPTER 7

CHAPTER 7

LUMBER STORAGE YARDS AND WOOD

PROCESSING PLANTS

Lumber Piling.—Lumber piling shall be on solid ground, or sawdust filing.—Start particles and product of the graze, and in orderly and regular piles.

Height of Piles.—Height of piles shall not be over (14) feet with due regard for stability.

Height of Piles.—Height of piles shall not be over (14) feet with due regard for stability.

I cet with due regard for stability.

Text with due regard for stability.

Storage or miles afform the every stable were referably of concrete piers, are milroad from. The minimum of bottoms shall be not less than (1) one foot above ground.

Divierags,—The driveways shall be so a panel maximum grid system units of fifth of the stability.

Storage Start Text Storage—There shall be located in a separate room and blower or dust collecting system.

Storage Start Text Storage—Each machine shall be connected to an amplitude with an effective more of the produced and alice shall be maintained clear to permit valy access to all parts of the graze, so \$800.5-1. Heating shall comply with the requirements of Section \$800.5-1. Heating shall comply with the requirements of Section \$800.5-1. Track Storage—Three shall be motivated in this ordinates are under the substance of a host orange or housing of earlies are substance of a hardeness and tummable instable substance of a substance of a hardeness and tummable instable substance of a substance of a hardeness and tummable instable substance of a substance of a substance of a substance of a substance

Construction of Lumber Storage Buildings.—Construction sist of masonry, all metal walls or equivalent construction nuous masonry foundations shall be used. Fire wall divisions provided (one hour fire rating) every 100 feet. Fire wall from foundation to not less than eightene (18) inches above

code of the City of Birmingham.

790.14 Resting—All heading equipment shall conform with established fire prevention standards. Salamanders, braziers, portable heaters or other open fires shall not be used.

790.15 Power Working Machines—Power woodworking machines and saws shall be located in separate masoury walled buildings with the standards for the Installation of Blower and Exhaust Systems for Dust, Stock, and Vapor Removal of the National Board of Fire Underwriters. If blower system and vault is not provided, then daily removal of sawdust, chips and shorts to a safe place of storage for the standards for the Installation of Blower and Exhaust and the standards for the Installation of Blower and Exhaust and the standards of sawdust, chips and shorts to a safe place of storage for the standards of swedust, chips and shorts to a safe place of storage for the standards of swedust, chips and shorts to a safe place of storage for the standards of Rubbish Handling and Interest or the National Fire Frotection Association. All stacks shall be provided with suitable still, the standards of Rubbish Handling and Interestors of the National Fire Frotection Association. All stacks shall be provided with suitable still, the standards of Rubbish Handling and Interestors of the National Fire Frotection Association. All stacks shall be provided with suitable still, the standards of Rubbish Handling and Interest to storage bin, with missed sall, shall be provided.

70.17 Shooking—Snooking shall be provided with suitable still provided with suitable still provided.

70.18 Rosking—Snooking shall be provided with suitable of Raskembly in number of occupancy in excess of the difference of the City of Birmingham shall be approximated and the still be suitable standards of the City of Birmingham shall be maintained in the Building Code of the City of Birmingham shall be maintained in Building Code of the City of Birmingham shall be maintained in Building Code of the City of Birmingham shall be maintained in Building Code of the C

specific locations designated as sate ror smoor-e unlawful and a violation of this ordinance for any such plant or posted area.

And—Weeds shall be kept down throughout be sprayed as often as needed with a satis-stance of the state of the state of the state of the one by weed killer, from the premises. Burning, combustible material on the premises is pro-

CHAPTER 8

GARAGES

CHAPTER 9 PUBLIC BUILDINGS, EXITS, ETC.

THE BIRMINGHAM (MICH.) ECCENTRIC

THE BIRMINGHAM (MICR.) ECCENTRIC Jan. 22, 1959 7-D.
shall be provided for protection of rooms containing film.
900.09-9 Loose film and scraps shall be handled in accordance with
above requirements or removed from the building and disposed of.
Boilers, Furnaese, Heaters, Ranges, Elc., shall be installed and provided
with pressure relief valves, temperature controls, automatic shut offs,
cc. as recuired by the Building Code of the City of Birmingham.
900.11-1 In buildings coles in the City of Birmingham.
900.11-2 In buildings coles in the City of Birmingham.
900.11-2 In buildings coles in the Provided of the Companies of the standard of Colding type may be used, provided, that
not more than 7 seats of each side of side or 14 seats between any
2 aisless are provided. The seats are to be spaced not less than 26
inches from back to back. Where movable seats are used, such seats
must be secured together in groups of not less than three. Alsless
900.11-2 Mevable seats are prohibited in balcenies or galleries
having floors with steps. Where evita are located at the side of places
of public assembly having movable seats, there shall be a cross side
giving access to same.

MISCELLANEOUS

nied as a place of assembly and having

made and separation.

Heating.

Stoves and gas ranges shall be installed and maintained
manner as to avoid undue fire hazard.

Heating of Public Garages and High Hazard Use Group